

Coverfilm Antigraffiti - Glossy



COVERFILM ANTIGRAFFITI

Face Material

Gloss clear LH polyester.

Type	LH polyester
Colour and Finish	Gloss clear
Weight	28 g/m ² ± 10% ISO-536
Thickness	20 µ ± 10% ISO 534-80

Adhesive

Solvent based permanent acrylic adhesive featuring good water and cleaning agents resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	ASP8A permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/+140°C
Shear	Very high
Tack	High N/inch ²
Final Adhesion	Very high N/inch

Liner

Type	One side siliconised polyester
Colour and Finish	Clear
Weight	42 g/m ² ± 10% ISO 536
Thickness	30 µ ± 10% ISO 534
Transparency	>95 % DIN 53 147-64

Applications

Offers extreme high clarity, very high UV resistance and also has excellent anti-graffiti properties.

Printing Methods

Not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of 22° ± 2° and 50 ± CC 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.